



Van der Graaf  
Power Transmission Equipment



# TM127-25

**Drummotor**

**Product information**

[www.vandergraafpte.nl](http://www.vandergraafpte.nl)

## Selection table TM127-25

TYPE	Power (kW)	Beltspeed at 50 Hz (m/s) Beltpull (N)								Min. L (mm) Design A / B		Full load curr. at 400 V/50 Hz (A)	Weight L=350 (kg)
		2,60 400	2,00 525	1,70 615	1,30 805	1,00 1045	0,80 1305						
215 Z	1,10	2,60 400	2,00 525	1,70 615	1,30 805	1,00 1045	0,80 1305			300	325	2,2	20
215 PL2		0,60 1685	0,50 2025	0,40 2530	0,30 3165					350	375		
415 Z	1,10	1,30 805	1,00 1045	0,85 1230						325	350	2,8	21
210 Z	0,75	2,60 275	2,00 355	1,70 420						300	325	1,4	20
210 PL2		0,40 1725								350	375		
410 Z	0,75	1,30 550	1,00 715	0,85 840	0,65 1095	0,50 1425				300	325	1,9	20
410 PL2		0,30 2300	0,24 2875	0,20 3450	0,16 4100					350	375		
275 Z	0,55	2,60 200	2,00 260	1,70 305						275	300	1,1	18
475 Z	0,55	1,30 400	1,00 525	0,85 615	0,65 805	0,50 1045	0,40 1305			275	300	1,4	18
475 PL2		0,30 1685	0,24 2110	0,20 2530	0,16 3165					325	350		
405 Z	0,37	1,30 270	1,00 350	0,85 415	0,65 540	0,50 705	0,40 880	0,32 1100		275	300	1,0	17
405 PL2		0,20 1700	0,16 2130							325	350		
605 Z	0,37	0,25 1405								275	300	1,1	18
605 PL2		0,14 2430	0,11 3095							325	350		
434 Z	0,25	1,30 185	1,00 240	0,85 280	0,65 365	0,50 475	0,40 595	0,32 740		250	275	0,7	16
434 ST3-Z		0,25 930	0,20 1165	0,15 1550						275	300		
434 PL3		0,046 4100	0,036 4100	0,031 4100	0,024 4100					350	375		
634 ST3-Z	0,25	0,17 1370								300	325	0,8	18
634 PL2		0,14 1645	0,11 2090							325	350		
634 PL3		0,020 4100	0,016 4100							375	400		

Available standard facewidth's: 250 - 275 - 300 - 325 - 350 - 375 - 400 - 450 - 500 - 550 - 600 - 650 - 700 - 750 - 800 - 850 - 900 - 950 - 1000 mm.

Minimum facewidth can deviate, see cable exit options.

The total weight of a drummotor grows approx. 2,0 kg per 100 mm.

When an electro-mechanical brake is fitted, the minimum facewidth is increased by 75 mm.

Available torque Nm: (Beltpull N x Drumdiameter m) / 2

Beltpull/-torque max. : 4100 N / 260 Nm ( lmax upon request )

## Selection table TM127-25 Dahlander

TYPE	Power (kW)	Beltspeed at 50 Hz (m/s) Beltpull (N)								Min. L (mm) Design A / B		Full load curr. at 400 V/50 Hz (A)	Weight L=350 (kg)
		1,30/2,60 400/275	1,00/2,00 525/355	0,85/1,70 615/420	0,65/1,30 805/550	0,50/1,00 1045/715	0,40/0,80 1305/890						
475/210 Z	0,55/ 0,75	1,30/2,60 400/275	1,00/2,00 525/355	0,85/1,70 615/420	0,65/1,30 805/550	0,50/1,00 1045/715	0,40/0,80 1305/890			300	325	1,4/ 1,7	20
475/210 PL2		0,30/0,60 1685/1150	0,24/0,48 2110/1440	0,20/0,40 2530/1725	0,16/0,32 3165/2155					350	375		
437/275 Z	0,27/ 0,55	1,30/2,60 200	1,00/2,00 260	0,85/1,70 305	0,65/1,30 400	0,50/1,00 525	0,40/0,80 655	0,32/0,64 815		275	300	0,9/ 1,3	18
437/275 ST3-Z		0,25/0,50 1025	0,20/0,40 1280	0,15/0,30 1550						300	325		

Available standard facewidth's: 275 - 300 - 325 - 350 - 375 - 400 - 450 - 500 - 550 - 600 - 650 - 700 - 750 - 800 - 850 - 900 - 950 - 1000 mm.






Minimum facewidth can deviate, see cable exit options.

The total weight of a drummotor grows approx. 2,0 kg per 100 mm.

When an electro-mechanical brake is fitted, the minimum facewidth is increased by 75 mm.

Available torque Nm: (Beltpull N x Drumdiameter m) / 2

# Options

	Specification	Standard	Optional
 <h2>CONSTRUCTION</h2>	Shafts and bolts	Mild steel	Stainless steel
	Endflanges	Cast iron	Stainless steel
	Shell	Mild steel	Stainless steel
	Junctionbox	Cast iron	Stainless steel or polyamide
	Cable		Shielded or non-shielded
	Sealing mild steel	RB	RBS, HD-1
	Sealing stainless steel	CR	FS, HD-1, HD-2
 <h2>SHELL</h2>	Crowned	•	
	Cylindrical		•
	Balanced		•
	Lagging, cold vulcanised		•
	Lagging, hot vulcanised		•
	Lagging, FDA approved		•
	Fitted with grooves, patterns		•
	Sprockets		•
 <h2>ELECTRO MOTOR</h2>	Three-phase asynchronous	•	
	Power supply	230/400 V - 50 Hz	Other voltages and frequencies on request
	Two speed (Dahlander)		•
	Insulation class	F	•
	Thermal protection		Bi-metal or thermistor
	Run by frequency inverter	•	
 <h2>OTHER OPTIONS</h2>	Food grade oil		•
	Backstop, mechanical		•
	Brake, electro mechanical		•
	Inclined or vertical position		•
	Other facewidth's		•
	Different shaft designs		•
	Encoder or sensorbearing in drum motor		•
	Encoder or sensorbearing in tail drum		•
 <h2>CERTIFICATES</h2>	CE	•	
	UL		•
	CSA		•
	ATEX zone 22, dust		•
	IP69K		•

## Our drummotors, an overview

Drummotor type	Drum diameter (mm)	Shaft diameter (mm)	Power (kW)	Speed (m/s)	Beltpull (N)
TM80B20	80	20	0,07 - 0,12	0,11 - 1,15	598
TM100B25	100	25	0,08 - 0,37	0,007 - 3,60	1300
TM113B25	113	25	0,12 - 0,55	0,008 - 4,40	1150
TM127_25	127	25	0,25 - 1,10	0,016 - 2,60	4100
TM138_25	138	25	0,25 - 1,10	0,017 - 2,80	3800
TM160_25	160	25	0,25 - 0,75	0,31 - 3,30	1135
TM160_30	160	30	0,25 - 2,20	0,11 - 4,00	3000
TM215_30	215	30	0,25 - 2,20	0,27 - 5,30	1900
TM215_40	215	40	0,75 - 5,5	0,17 - 4,70	5115
TM215B50	215	50	1,5 - 7,0	0,18 - 0,62	11500
TM273_40	273	40	0,75 - 5,50	0,21 - 5,00	4355
TM315_40	315	40	0,75 - 5,50	0,40 - 5,20	4020
TM315_50	315	50	2,2 - 11,0	0,34 - 4,40	7125
TM315B60	315	60	3,0 - 11,0	0,22 - 1,40	12790
TM400_50	400	50	2,2 - 11,0	0,40 - 4,80	5700
TM400_60	400	60	3,0 - 22,0	0,45 - 4,20	10960
TM500_60	500	60	3,0 - 22,0	0,55 - 4,40	8905
TM500A75	500	75	15,0 - 30,0	1,00 - 3,20	14250
TM500A100	500	100	15,0 - 30,0	0,55 - 1,25	25300
TM620A75	620	75	15,0 - 30,0	1,25 - 3,90	11400
TM630A100	630	100	37,0 - 55,0	1,60 - 4,00	21970
TM800A100	800	100	37,0 - 55,0	2,00 - 5,10	17575
TM800A130	800	130	55,0 - 132,0	2,00 - 4,50	35625

### Contact us

Van der Graaf B.V.  
De Weijert 14  
8325 EM Vollenhove  
The Netherlands  
Tel.: 0031 527 241 441  
sales@vandergraafpte.nl

### Representatives

Check our website for your regional representative  
[www.vandergraafpte.nl](http://www.vandergraafpte.nl)