



Van der Graaf  
Power Transmission Equipment



# TM630A100

Drummotor

Product information

[www.vandergraafpte.nl](http://www.vandergraafpte.nl)



## Selection table TM630A100






TYPE	Power (kW)	Beltspeed at 50 Hz (m/s) Beltpull (N)										Min. L (mm) Design A	Full load curr. at 400 V/50 Hz (A)	Weight L=1000 (kg)
		4,00 13065	3,15 16585	2,50 20900										
475 Z	55,00											1000	93	1100
460 Z	45,00	4,00 10690	3,15 13570	2,50 17100	2,00 21375							1000	76	1075
650 Z	37,00	4,00 8790	3,15 11160	2,50 14060	2,00 17575	1,60 21970						1000	68	1100

The total weight of a drummotor grows approx. 45 kg per 100 mm.

Weight of a drummotor includes the brackets.

Available torque Nm: (Beltpull N x Drumdiameter m) / 2

# Options

	Specification	Standard	Optional
 <b>CONSTRUCTION</b>	Shafts and bolts	Mild steel	
	Bolts	Mild steel	Stainless steel
	Endflanges	Cast iron	
	Shell	Mild steel	
	Junctionbox	Mild steel	
	Cable		Shielded or non-shielded
	Sealing mild steel	MFS	MFS
	Sealing stainless steel	MFS	MFS
 <b>SHELL</b>	Crowned	•	
	Cylindrical		•
	Lagging, cold vulcanised		•
	Lagging, hot vulcanised		•
	Lagging, FDA approved		•
	Fitted with grooves, patterns		•
 <b>ELECTRO MOTOR</b>	Three-phase asynchronous	•	
	Power supply	400/690 V - 50 Hz	Other voltages and frequencies on request
	Twin drive (double power)		•
	Insulation class	F	H
	Thermal protection		Bi-metal or thermistor
	Run by frequency inverter	•	
 <b>OTHER OPTIONS</b>	Food grade oil		•
	Backstop, mechanical		•
	Other facewidth's		•
	Different shaft designs		•
 <b>CERTIFICATES</b>	CE	•	
	UL		•
	CSA		•
	ATEX zone 22, dust		•

## Our drummotors, an overview

Drummotor type	Drum diameter (mm)	Shaft diameter (mm)	Power (kW)	Speed (m/s)	Beltpull (N)
TM80B20	80	20	0,07 - 0,12	0,11 - 1,15	598
TM100B25	100	25	0,08 - 0,37	0,007 - 3,60	1300
TM113B25	113	25	0,12 - 0,55	0,008 - 4,40	1150
TM127_25	127	25	0,25 - 1,10	0,016 - 2,60	4100
TM138_25	138	25	0,25 - 1,10	0,017 - 2,80	3800
TM160_25	160	25	0,25 - 0,75	0,31 - 3,30	1135
TM160_30	160	30	0,25 - 2,20	0,11 - 4,00	3000
TM215_30	215	30	0,25 - 2,20	0,27 - 5,30	1900
TM215_40	215	40	0,75 - 5,5	0,17 - 4,70	5115
TM215B50	215	50	1,5 - 7,0	0,18 - 0,62	11500
TM273_40	273	40	0,75 - 5,50	0,21 - 5,00	4355
TM315_40	315	40	0,75 - 5,50	0,40 - 5,20	4020
TM315_50	315	50	2,2 - 11,0	0,34 - 4,40	7125
TM315B60	315	60	3,0 - 11,0	0,22 - 1,40	12790
TM400_50	400	50	2,2 - 11,0	0,40 - 4,80	5700
TM400_60	400	60	3,0 - 22,0	0,45 - 4,20	10960
TM500_60	500	60	3,0 - 22,0	0,55 - 4,40	8905
TM500A75	500	75	15,0 - 30,0	1,00 - 3,20	14250
TM500A100	500	100	15,0 - 30,0	0,55 - 1,25	25300
TM620A75	620	75	15,0 - 30,0	1,25 - 3,90	11400
TM630A100	630	100	37,0 - 55,0	1,60 - 4,00	21970
TM800A100	800	100	37,0 - 55,0	2,00 - 5,10	17575
TM800A130	800	130	55,0 - 132,0	2,00 - 4,50	35625

### Contact us

Van der Graaf B.V.  
De Weijert 14  
8325 EM Vollenhove  
The Netherlands  
Tel.: 0031 527 241 441  
sales@vandergraafpte.nl

### Representatives

Check our website for your regional representative  
[www.vandergraafpte.nl](http://www.vandergraafpte.nl)